Sensor, SpaceLogic SLA Series, room, humidity, temperature, segmented LCD, analog outputs with optimum white housing

SLAWLX2

Main

wain	
Range	SpaceLogic
Product or component type	Sensor
Product name	SpaceLogic Room Unit
Type of measurement	Humidity Temperature
Device application	HVAC Temperature control Fan speed controller
Product specific application	Humidity control
Product certifications	CE conforming to EN 61000-6-2 CE conforming to EN 61000-6-3 CE conforming to EN 61326-1 RCM EAC ICES-003 CULus
Display size	2 inch
Display type	LCD display
Information displayed	Temperature Temperature set point Menu-driven user interface Relative humidity
Location	Living space
Mounting support	Wall-mount
Depth	23.7 mm
Height	85 mm
Width	115 mm
Network frequency	50 Hz 60 Hz
Ambient air temperature for operation	050 °C
Standards	UL 916 FCC part 15 class B
Colour	White
Sensor type	Transmitter Thin-film capacitive
[Us] rated supply voltage	24 V AC 2030 V DC

Device presentation	Complete product
Surface finish	Glossy
_	
Complementary	
Communication network type	Wired
Control type	+ button - button Arrow button
Material	ABS (acrylonitrile butadiene-styrene)
Function available	With temperature sensor With humidity sensor
Hysteresis	1.5 %
Connections - terminals	Screw terminal - 2 cable(s) (AWG 24AWG 18)
Number of outputs	1 fan 1 configurable
Output type	Analog
Output voltage	010 V for fan speed 05 V for configurable analog output 010 V for configurable analog output
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers
Environment	
Humidity setting range	0100 %
Temperature setting range	1035 °C 050 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.8 cm
Package 1 Width	9.67 cm
Package 1 Length	14.0 cm
Package 1 Weight	181.82 g
	181.82 g
Offer Sustainability	
Offer Sustainability Sustainable offer status	Green Premium product
Offer Sustainability Sustainable offer status REACh Regulation	Green Premium product REACh Declaration
Offer Sustainability Sustainable offer status	Green Premium product
Offer Sustainability Sustainable offer status REACh Regulation	Green Premium product REACh Declaration Compliant
Offer Sustainability Sustainable offer status REACh Regulation EU RoHS Directive	Green Premium product REACh Declaration Compliant EU RoHS Declaration
Offer Sustainability Sustainable offer status REACh Regulation EU RoHS Directive Mercury free	Green Premium product REACh Declaration Compliant EU RoHS Declaration Yes
Offer Sustainability Sustainable offer status REACh Regulation EU RoHS Directive Mercury free China RoHS Regulation	Green Premium product REACh Declaration Compliant EU RoHS Declaration Yes China RoHS declaration
Offer Sustainability Sustainable offer status REACh Regulation EU RoHS Directive Mercury free China RoHS Regulation RoHS exemption information	Green Premium product REACh Declaration Compliant EU RoHS Declaration Yes China RoHS declaration Yes

Recommended replacement(s)