SIEMENS

Data sheet

6GK7545-1GX00-0XE0

product type designation



CP 1545-1

Communications processor CP 1545-1 for connection of SIMATIC S7-1500 to Industrial Ethernet, TCP/IP, UDP, S7 communication, Security (firewall), SNMPv1/v3, DHCP, FTP client/server, email, IPv4/IPv6, time-of-day synchronization via NTP, connection to cloud systems via MQTT, 1x RJ45 (10/100/1000 Mbit/s).

transfer rate	
transfer rate	
 at the 1st interface 	10 1000 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	1
number of electrical connections	
at the 1st interface / according to Industrial Ethernet	1
type of electrical connection	
at the 1st interface / according to Industrial Ethernet	RJ45 port
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	15 V
relative symmetrical tolerance / at DC	
• at 15 V	3 %
consumed current	
from backplane bus / at DC / at 15 V / typical	0.3 A
power loss [W]	4.5 W
ambient conditions	
ambient temperature	
 for vertical installation / during operation 	0 40 °C
 for horizontally arranged busbars / during operation 	0 60 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1500 single width
width	35 mm
height	142 mm
depth	129 mm
net weight	0.32 kg
fastening method	
S7-1500 rail mounting	Yes
product features, product functions, product components	/ general
number of units	
per CPU / maximum	8

• note	depending on CPU type
product functions / cloud connectivity	
protocol / is supported	
Message Queuing Telemetry Transport (MQTT)	Yes
 Advanced Message Queuing Protocol (AMQP) 	No
product function / for cloud connectivity	
 trigger management 	Yes
time stamping	Yes
product feature / for cloud connectivity / buffered message frame memory	No
number of data points per device / maximum	500
performance data / open communication	
number of possible connections / for open communication	
by means of T blocks / maximum	118; depending on the system upper limit
data volume	
as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum	65536 byte
number of Multicast stations	118
performance data / S7 communication	
number of possible connections / for S7 communication	
• maximum	118; depending on the system upper limit
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	118
performance data / IT functions	
number of possible connections	
as client / by means of FTP / maximum	32
as server / by means of FTP / maximum	16
number of possible connections	
as server / by means of HTTP / maximum	4
as email client / maximum	1
data volume / as user data for email / maximum	64 Kibyte
performance data / telecontrol	
protocol / is supported	v.
• TCP/IP	Yes
product functions / management, configuration, engineeri	
product function / MIB support	Yes
protocol / is supported • SNMP v1	Voc
	Yes
SNMP v3 DCP	Yes Yes
• LLDP	Yes
	100
contiguration software	
configuration software • required	
• required	STEP 7 Professional V15.1 (TIA Portal) or higher
required identification & maintenance function	
required identification & maintenance function I&M0 - device-specific information	STEP 7 Professional V15.1 (TIA Portal) or higher
required identification & maintenance function I&M0 - device-specific information I&M1 - higher level designation/location designation	STEP 7 Professional V15.1 (TIA Portal) or higher Yes
required identification & maintenance function I&M0 - device-specific information I&M1 - higher level designation/location designation product functions / diagnostics	STEP 7 Professional V15.1 (TIA Portal) or higher Yes
	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes
required identification & maintenance function I&M0 - device-specific information I&M1 - higher level designation/location designation product functions / diagnostics product function / web-based diagnostics product functions / routing	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes Yes; via S7-1500 CPU
	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes
required identification & maintenance function I&M0 - device-specific information I&M1 - higher level designation/location designation product functions / diagnostics product function / web-based diagnostics product functions / routing service / routing / note product function	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes Yes; via S7-1500 CPU
	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes Yes; via S7-1500 CPU IP routing up to 1 Mbps
required identification & maintenance function I&M0 - device-specific information I&M1 - higher level designation/location designation product functions / diagnostics product function / web-based diagnostics product functions / routing service / routing / note product function static IP routing static IP routing IPv6	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes Yes; via S7-1500 CPU IP routing up to 1 Mbps Yes
	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes Yes; via S7-1500 CPU IP routing up to 1 Mbps Yes No
required identification & maintenance function I&M0 - device-specific information I&M1 - higher level designation/location designation product functions / diagnostics product function / web-based diagnostics product functions / routing service / routing / note product function static IP routing static IP routing IPv6 dynamic IP routing	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes Yes; via S7-1500 CPU IP routing up to 1 Mbps Yes No No
	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes Yes; via S7-1500 CPU IP routing up to 1 Mbps Yes No No
required identification & maintenance function I&M0 - device-specific information I&M1 - higher level designation/location designation product functions / diagnostics product function / web-based diagnostics product functions / routing service / routing / note product function static IP routing static IP routing IPv6 dynamic IP routing IPv6 protocol / is supported	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes Yes; via S7-1500 CPU IP routing up to 1 Mbps Yes No No No
	STEP 7 Professional V15.1 (TIA Portal) or higher Yes Yes Yes; via S7-1500 CPU IP routing up to 1 Mbps Yes No No No No

OSPFv2	No
OSPFv3 for IPv6	No
• VRRP	No
VRRP for IPv6	No
• BGP	No
• PPP	No
PPoE via DSL	No
product functions / security	
firewall version	stateful inspection
product function	
password protection for Web applications	No
ACL - IP-based ACL - IP-based	No
ACL - IP-based for PLC/routing	No
switch-off of non-required services blacking of communication via abunical parts	Yes
blocking of communication via physical ports	No V
log file for unauthorized access	Yes
product functions / time	
product function / SICLOCK support	No
product function / pass on time synchronization	Yes
protocol / is supported	V
• NTP	Yes
standards, specifications, approvals / hazardous environn	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
according to GB standard	
further information / internet-Links	
further information / internet-Links	http://www.siemens.com/tia-selection-tool
further information / internet-Links Internet-Link	http://www.siemens.com/simatic-net
further information / internet-Links Internet-Link • to web page: selection aid TIA Selection Tool	http://www.siemens.com/simatic-net https://mall.industry.siemens.com
Internet-Link • to web page: selection aid TIA Selection Tool • to website: Industrial communication	http://www.siemens.com/simatic-net
Internet-Link Internet-Link to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall	http://www.siemens.com/simatic-net https://mall.industry.siemens.com
Internet-Link • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager	http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax
Internet-Link • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support	http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb
Internet-Link • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager	http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax
Internet-Link • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support	http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax