

SIMATIC S7-1200, Digital output SM 1222, 16 DO, 24 V DC, sourcing (Sinking Output), NPN transistor 0.5 A



General information	
Product type designation	SM 1222, DO 16x 24 V DC/0.5 A Sink
Supply voltage	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	140 mA
Power loss	
Power loss, typ.	2.5 W
Digital outputs	
Number of digital outputs	16
• in groups of	1
Current-sinking	Yes
Short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	Typ 45 V
Switching capacity of the outputs	
• with resistive load, max.	0.5 A

• on lamp load, max.	5 W
Output voltage	
• Rated value (DC)	24 V
• for signal "0", max.	L+ minus 0.75 V DC with 10k Load
• for signal "1", min.	0,5 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "0" residual current, max.	75 µA
Output delay with resistive load	
• "0" to "1", max.	20 µs
• "1" to "0", max.	350 µs
Total current of the outputs (per group)	
horizontal installation	
— up to 50 °C, max.	8 A; Current per mass
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	0.5 A
— on lamp load, max.	5 W
— with resistive load, max.	0.5 A
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
Diagnostics indication LED	
• for status of the outputs	Yes
Potential separation	
Potential separation digital outputs	
• between the channels, in groups of	1
• between the channels and backplane bus	500 V AC
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes

Marine approval	Yes
-----------------	-----

Ambient conditions

Ambient temperature during operation

• min.	-20 °C
• max.	60 °C
• horizontal installation, min.	-20 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-20 °C
• vertical installation, max.	50 °C
• permissible temperature change	5°C to 55°C, 3°C / minute

Ambient temperature during storage/transportation

• min.	-40 °C
• max.	70 °C

Air pressure acc. to IEC 60068-2-13

• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa

Relative humidity

• Operation at 25 °C without condensation, max.	95 %
---	------

Connection method

required front connector	Yes
--------------------------	-----

Mechanics/material

Enclosure material (front)	
• Plastic	Yes

Dimensions

Width	45 mm
Height	100 mm
Depth	75 mm

Weights

Weight, approx.	220 g
-----------------	-------

last modified: 10/13/2020