



Main

Range of product	ARGUS presence detector
Range	ARGUS
Product or component type	Presence detector
Load type	Halogen lamp: 2000 W, AC Motor: : 1000 VA, AC Capacitive: : 10 A, 140 µF, AC Incandescent lamp: 2200 W, AC Low voltage halogen lamp with wire-wound transformer: : 500 VA, AC Low voltage halogen lamp with electronic transformer: : 1050 VA, AC Energy saving lamp: : 100 VA
Colour tint	Polar white
Colour code	RAL 9010
Type of packing	Carton

Complementary

[Ue] rated operational voltage	220/230 V
Network frequency	50/60 Hz
Input compatibility	Push-buttons and electronic insert
[Ue] rated operational voltage	220/230 V
Input function	2 x external triggering over PL
Output current	4 A 10 A
Number of channels	2
Type of setting	Time adjustment Light sensitivity adjustable
Control type	Remote control
Function available	Master function
Time delay	10 s...30 min 5...120 min
Light intensity adjustment	10...1000 lux
Horizontal detection angle	0...360 °
Detection range	Radius: 7 m
Material	PC (polycarbonate) brilliant

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Device mounting	Ceiling
Mounting height	2.5 m

Environment

IP degree of protection	IP20
Ambient air temperature for operation	0...25 °C
Environmental health and issues	Halogen free

Packing Units

Package 1 Weight	162.000 g
Package 1 Height	67.000 mm
Package 1 width	105.000 mm
Package 1 Length	105.000 mm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins