

## PNOZ X7 24VACDC 2n/o

774059



Safety relay (standalone), inputs: 1-channel wiring, outputs: 2 N/O, automatic/manual start, UB 24 V AC/DC, width: 22.5 mm, screw terminals integrated, monitoring of E-STOP, safety gates.

## Technical details

### General data

Approval: CCC, CE, UKCA, cULus Listed, KOSHA, EAC (Eurasian), TÜV

### Technical data

#### Environment

RoHS directive: 2011/65/EU, 2015/863/EU

RoHS conformity: 0

RoHS exceptions: 0

RoHS except.s acc. to direct.: 7A, 7C I

REACH compliance: 1

REACH included substances: Blei, Bleioxid

%-part of the pollutant: > 0,1%

CAS No.: 7439-92-1, 1317-36-8

SCIP entry available: yes

WEEE classification (08/2018): 5 devices (feed size < 50cm)

### Commercial data

ECLASS version: ECLASS-13

ECLASS Reference Feature: 27371819

ETIM Version: ETIM-9.0

ETIM Reference Group: EG000019

ETIM Reference Feature: EC001449

UNSPSC 25:	39122331
GTIN:	4046548012309
Volume:	0.255 dm3
Harmonized System Code:	85364900
Type of tariff number:	TARIC
Use of customs tariff number:	export, Import
Quantity per packaging unit:	1