Product datasheet

Specifications

Dimming actuator, SpaceLogic KNX, Universal, Master 2 channel, white

MTN6710-0102

Main

Product or component type	Dimming actuator
Operating mode	KNX bus system
Bus type	KNX

Complementary

Mounting support	DIN rail
[Ue] rated operational voltage	230 V
Network frequency	50/60 Hz
Number of outputs	2
Load type	LV halogen: 20...350 W at 230 V Incandescent lamp: 20...350 W at 230 V Halogen lamp: 20...350 W at 230 V RC LED lamp: 2...200 W at 230 V RL LED lamp: 2...60 W at 230 V

Environment

IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.400 cm
Package 1 Width	12.800 cm
Package 1 Length	15.900 cm
Package 1 Weight	269.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	28
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	8.350 kg

Contractual warranty

Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Apr 4, 2025

Environmental Data explained ›

How we assess product sustainability ›

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	**25**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**

Use Again

Repack and remanufacture

Circularity Profile	**End of Life Information**
Take-back	**No**

Life Is On | Schneider Electric