



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8226-1HF40-2BD2-Z**
G14

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

| | | P _N [kW] | M _N [Nm] | I _N [A] | U _N [V] | f _N [Hz] | n _N [rpm] | M _{max} [Nm] | I _{max} [A] | n _{max} [rpm] | M ₀ [Nm] | I ₀ [A] | η | cos φ | I _μ [A] |
|---|------------------|------------------------|------------------------|-----------------------|-----------------------|------------------------|-------------------------|--------------------------|-------------------------|---------------------------|------------------------|-----------------------|-------|-------|-----------------------|
| Y | ALM 400V | 200.0 | 1,091.0 | 350.0 | 390 | 59.0 | 1,750 | 1,850 | 580.0 | 4,500 | 1,091.0 | 350 | 0.954 | 0.890 | 114.0 |
| | BLM/SLM 400V | 175.0 | 1,114.0 | 350.0 | 340 | 50.7 | 1,500 | 1,850 | 580.0 | 4,500 | 1,114.0 | 350 | 0.950 | 0.890 | 117.0 |
| | ALM/BLM/SLM 480V | 220.0 | 1,051.0 | 335.0 | 450 | 67.3 | 2,000 | 1,850 | 580.0 | 4,500 | 1,051.0 | 335 | 0.957 | 0.880 | 117.0 |

Mechanical data

| | |
|---------------------------|---|
| Motor type | Squirrel cage asynchronous motor |
| Shaft height | 225 |
| Cooling | Open circuit cooling NDE-> DE |
| Vibration severity grade | R/A |
| Shaft and flange accuracy | R |
| Degree of protection | IP23 |
| Design acc. to Code I | IM B3 (IM B6, IM B7, IM B8, IM V6) |
| Temperature monitoring | Pt1000 temperature sensor in the stator winding |
| Color | Standard (Anthracite RAL 7016) |
| Type of the bearing | Standard |
| Shaft end | Feather key with half key balancing |
| Encoder system | Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm |

Physical constants

| | |
|-----------------------|--------------------------|
| Thermal time constant | 23 min |
| Moment of inertia | 19,300 kgcm ² |
| Weight (approx.) | 740 kg |

Connection

| | |
|-------------------------------|--------------|
| Type of electrical connection | Terminal box |
| Position of the connection | NDE top |
| Power connection | DE |
| Signal connection | right |
| Terminal box designation | 1XB7700-P02 |

Cooling data and sound pressure level

| | |
|---|------------------------|
| Airflow, min. | 0.33 m ³ /s |
| Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB | 73 dB ¹⁾ |
| Air discharge | axial |
| Pressure drop | 600 Pa |

External fan

Max. power consumption

1 AC 200 ... 277 V (±10%) 50/60 Hz ±10% 2.0 ... 2.3 A

Special design

G14 with air filter

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 2000 rpm