



Figure similar

SIMATIC S7-1500, digital output module DQ 8xAC 230V/5A ST; relay; 8 channels in groups of 1; 5 A per group; diagnostics; substitute value: switching cycle counter for integrated relay, the module supports the safety-oriented shutdown of load groups up to SIL1 according to EN IEC 62061:2021 and Category 2 / PL c according to EN ISO 13849-1:2015. front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	DQ 8x230 V AC/5 A ST (relay)
HW functional status	From FS02
Firmware version	V2.1.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V12 / V12
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No
<ul style="list-style-type: none"> <li>PWM</li> </ul>	No
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No
<ul style="list-style-type: none"> <li>MSO</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Integrated operating cycle counter</li> </ul>	Yes; FW V2.1.0 or higher
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	80 mA
output voltage / header	
Rated value (AC)	230 V; 24 V DC to 120 V DC / 24 V AC to 230 V AC
Power	
Power available from the backplane bus	0.8 W
Power loss	
Power loss, typ.	5 W
Digital outputs	
Type of digital output	Relays
Number of digital outputs	8

Current-sinking	Yes
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	No
Controlling a digital input	Yes; possible
Size of motor starters according to NEMA, max.	5
<b>Switching capacity of the outputs</b>	
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	1 500 W; 10 000 operating cycles
<ul style="list-style-type: none"> <li>Low energy/fluorescent lamps with electronic control gear</li> </ul>	10x 58 W (25 000 operating cycles)
<ul style="list-style-type: none"> <li>Fluorescent tubes, conventionally compensated</li> </ul>	1x 58 W (25 000 operating cycles)
<ul style="list-style-type: none"> <li>Fluorescent tubes, uncompensated</li> </ul>	10x 58 W (25 000 operating cycles)
<b>Output current</b>	
<ul style="list-style-type: none"> <li>for signal "1" rated value</li> </ul>	5 A
<ul style="list-style-type: none"> <li>for signal "1" permissible range, min.</li> </ul>	5 mA; 10 V
<ul style="list-style-type: none"> <li>for signal "1" permissible range, max.</li> </ul>	8 A; thermal continuous current
<ul style="list-style-type: none"> <li>for signal "0" residual current, max.</li> </ul>	0 A
<b>Parallel switching of two outputs</b>	
<ul style="list-style-type: none"> <li>for logic links</li> </ul>	Yes
<ul style="list-style-type: none"> <li>for uprating</li> </ul>	No
<ul style="list-style-type: none"> <li>for redundant control of a load</li> </ul>	Yes
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	2 Hz
<ul style="list-style-type: none"> <li>with inductive load, max.</li> </ul>	0.5 Hz
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	2 Hz
<b>Total current of the outputs</b>	
<ul style="list-style-type: none"> <li>Current per channel, max.</li> </ul>	8 A; see additional description in the manual
<ul style="list-style-type: none"> <li>Current per group, max.</li> </ul>	8 A; see additional description in the manual
<ul style="list-style-type: none"> <li>Current per module, max.</li> </ul>	64 A; see additional description in the manual
<b>Relay outputs</b>	
<ul style="list-style-type: none"> <li>Number of relay outputs</li> </ul>	8
<ul style="list-style-type: none"> <li>Rated supply voltage of relay coil L+ (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>Current consumption of relays (coil current of all relays), typ.</li> </ul>	80 mA
<ul style="list-style-type: none"> <li>external protection for relay outputs</li> </ul>	With miniature circuit breaker with characteristic B for: $\cos \varphi$ 1.0: 600 A $\cos \varphi$ 0.5 ... 0.7: 900 A with 8 A Diazed fuse: 1 000 A
<ul style="list-style-type: none"> <li>Contact connection (internal)</li> </ul>	No
<ul style="list-style-type: none"> <li>Number of operating cycles, max.</li> </ul>	4 000 000; see additional description in the manual
<ul style="list-style-type: none"> <li>Relay approved acc. to UL 508</li> </ul>	Yes; 250 V AC/5 A g.p.; 120 V AC TV-4 tungsten; A300, R300
<b>Switching capacity of contacts</b>	
<ul style="list-style-type: none"> <li>with inductive load, max.</li> </ul>	see additional description in the manual
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	see additional description in the manual
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	600 m
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
Substitute values connectable	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	Yes
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Wire-break</li> </ul>	No
<ul style="list-style-type: none"> <li>Short-circuit</li> </ul>	No
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>RUN LED</li> </ul>	Yes; green LED
<ul style="list-style-type: none"> <li>ERROR LED</li> </ul>	Yes; red LED
<ul style="list-style-type: none"> <li>MAINT LED</li> </ul>	Yes; Yellow LED
<ul style="list-style-type: none"> <li>Monitoring of the supply voltage (PWR-LED)</li> </ul>	Yes; green LED
<ul style="list-style-type: none"> <li>Channel status display</li> </ul>	Yes; green LED
<ul style="list-style-type: none"> <li>for channel diagnostics</li> </ul>	No

• for module diagnostics	Yes; red LED
<b>Potential separation</b>	
Potential separation channels	
• between the channels	Yes; Switching of different phases permitted
• between the channels, in groups of	1
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
<b>Permissible potential difference</b>	
between different circuits	250 V AC between the channels and the supply voltage L+, 250 V AC between the channels and the backplane bus; 250 V AC between the channels (500 V AC when connecting different phases; basic insulation)
<b>Isolation</b>	
Isolation tested with	between the channels: 3 100 V DC; between the channels and the backplane bus: 3 100 V DC; between the channels and the supply voltage L+: 3 100 V DC; between the L+ and the backplane bus: 707 V DC (type test)
<b>Standards, approvals, certificates</b>	
Suitable for safety functions	No
Suitable for safety-related tripping of standard modules	Yes; From FS03
Highest safety class achievable for safety-related tripping of standard modules	
• Performance level according to ISO 13849-1	PL c
• Category according to ISO 13849-1	Cat. 2
<b>Ambient conditions</b>	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C; From FS03
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C; From FS03
• vertical installation, max.	40 °C
<b>Dimensions</b>	
Width	35 mm
Height	147 mm
Depth	129 mm
<b>Weights</b>	
Weight, approx.	350 g
<b>last modified:</b>	7/28/2021 