



SIMATIC FDE Gateway V1 Field Data Enabler / OT gateway for cloud connections
 1xDI 12/24 V - 1xDQ 24 V 1xAI 0...10 V or 4...20 mA 2x 10/100 Mbps 24 V DC
 industrial power supply

General information	
Product type designation	SIMATIC FDE Gateway V1
Installation type/mounting	
Design	IoT Gateway, built-in unit
Supply voltage	
Type of supply voltage	12 V DC to 24 V DC
Rated value (DC)	24 V
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	10 ms; according to IEC 61131-2 (6.2.1.3) severity degree PS2
Input current	
Current consumption, max.	0.6 A
Memory	
Capacity of main memory, max.	16 Mbyte
Digital inputs	
Number of digital inputs	1
Input voltage	
<ul style="list-style-type: none"> Type of input voltage for signal "0" for signal "1" 	DC 0 ... 5 V > 12 V DC
Input current	
<ul style="list-style-type: none"> for signal "0", max. (permissible quiescent current) for signal "1", typ. 	2.26 mA 2.26 mA
Digital outputs	
Type of digital output	open collector
Number of digital outputs	1
Short-circuit protection	Yes
Output voltage	
<ul style="list-style-type: none"> Type of output voltage permissible voltage at output, min. permissible voltage at output, max. 	DC 9.2 V 28 V
Output current	
<ul style="list-style-type: none"> for signal "1" rated value 	0.3 A
Analog inputs	
Number of analog inputs	1
Input ranges	
<ul style="list-style-type: none"> Voltage Current 	Yes; 0 to 10V Yes; 0 to 20 mA
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> 0 to +10 V 	Yes
Input ranges (rated values), currents	

• 0 to 20 mA	Yes
Interfaces	
Number of industrial Ethernet interfaces	2; 2x Ethernet (RJ45)
Industrial Ethernet	
• Industrial Ethernet interface — 100 Mbps	Yes
Protocols	
Protocols (Ethernet)	
• TCP/IP	Yes
• DHCP	Yes
Integrated Functions	
Monitoring functions	
• Status LEDs	10x LEDs
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	No
UL approval	No
RCM (formerly C-TICK)	Yes; in preparation
CCC	Yes; in preparation
EMC	CE (industry)
Ambient conditions	
Ambient temperature during operation	
• min.	-30 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
Relative humidity	
• Relative humidity	5 ... 85 % at 30 °C, no condensation
• Operation, max.	85 %
Dimensions	
Width	18 mm
Height	90 mm
Depth	76.6 mm

last modified: 8/11/2023 