

### product type designation

**CP 342-5**

Communications processor CP 342-5 for connection of SIMATIC S7-300 to PROFIBUS DP, S5-compatible, PG/OP and S7 communication.



### transfer rate

transfer rate

- at the 1st interface / according to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

### interfaces

number of interfaces / according to Industrial Ethernet	0
number of electrical connections	
• at the 1st interface / according to PROFIBUS	1
• for power supply	1
type of electrical connection	
• at the 1st interface / according to PROFIBUS	9-pin Sub-D socket (RS485)
• for power supply	4-pole terminal block

### supply voltage, current consumption, power loss

type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current	
• from backplane bus / at DC / at 5 V / typical	0.15 A
• from external supply voltage / at DC / at 24 V / typical	0.25 A
power loss [W]	6.75 W

### ambient conditions

ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

### design, dimensions and weights

module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.3 kg

### product features, product functions, product components / general

number of units

<ul style="list-style-type: none"> <li>per CPU / maximum</li> </ul>	4
<b>performance data / open communication</b>	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum data volume	16
<ul style="list-style-type: none"> <li>as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	240 byte
<b>performance data / PROFIBUS DP</b>	
service / as DP master	
<ul style="list-style-type: none"> <li>DPV0</li> </ul>	Yes
number of DP slaves	
<ul style="list-style-type: none"> <li>on DP master / operable</li> </ul>	124
data volume	
<ul style="list-style-type: none"> <li>of the address range of the inputs / as DP master / total</li> </ul>	2160 byte
<ul style="list-style-type: none"> <li>of the address range of the outputs / as DP master / total</li> </ul>	2160 byte
<ul style="list-style-type: none"> <li>of the address range of the inputs / per DP slave</li> </ul>	244 byte
<ul style="list-style-type: none"> <li>of the address range of the outputs / per DP slave</li> </ul>	244 byte
<ul style="list-style-type: none"> <li>of the address range of the diagnostic data / per DP slave</li> </ul>	240 byte
service / as DP slave	
<ul style="list-style-type: none"> <li>DPV0</li> </ul>	Yes
data volume	
<ul style="list-style-type: none"> <li>of the address range of the inputs / as DP slave / total</li> </ul>	240 byte
<ul style="list-style-type: none"> <li>of the address range of the outputs / as DP slave / total</li> </ul>	240 byte
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> <li>maximum</li> </ul>	16
<b>performance data / multi-protocol mode</b>	
number of active connections / with multi-protocol mode	
<ul style="list-style-type: none"> <li>without DP / maximum</li> </ul>	32
<ul style="list-style-type: none"> <li>with DP / maximum</li> </ul>	28
<b>performance data / telecontrol</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>TCP/IP</li> </ul>	No
<b>product functions / management, configuration, engineering</b>	
configuration software	
<ul style="list-style-type: none"> <li>required</li> </ul>	STEP 7 V5.1 SP2 or higher / STEP 7 Professional V12 (TIA Portal) or higher
<b>standards, specifications, approvals / hazardous environments</b>	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
<b>further information / internet-Links</b>	
Internet-Link	
<ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> <li>to website: Industrial communication</li> <li>to website: Industry Mall</li> <li>to website: Information and Download Center</li> <li>to website: Image database</li> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial

security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

7/7/2022 