

product type designation



CP 343-1

Communications processor CP 343-1 for connection of SIMATIC S7-300 to Industrial Ethernet via ISO and TCP/IP, PROFINET IO controller or PROFINET IO device, integrated 2-port switch ERTEC 200, S7 communication, fetch/write, SEND/RECEIVE RFC1006, multicast, DHCP, NTC- CPU sync, with and without diagnostics, initialization via LAN, 2x RJ45 connection for LAN with 10/100 Mbit/s.

transfer rate	
transfer rate	
<ul style="list-style-type: none"> at the 1st interface 	10 ... 100 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	2
number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet for power supply 	2 1
type of electrical connection	
<ul style="list-style-type: none"> of Industrial Ethernet interface at the 1st interface / acc. to Industrial Ethernet 	RJ45 port RJ45 port
type of electrical connection	
<ul style="list-style-type: none"> for power supply 	2-pole plugable terminal block
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage	24 V
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 5 V / typical from external supply voltage / at DC / at 24 V / typical from external supply voltage / at DC / at 24 V / maximum 	0.2 A 0.16 A 0.2 A
power loss [W]	5.8 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> for vertical installation / during operation for horizontally arranged busbars / during operation during storage during transport 	0 ... 40 °C 0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	

module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.22 kg
fastening method	
<ul style="list-style-type: none"> • S7-300 rail mounting 	Yes
performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
data volume	
<ul style="list-style-type: none"> • as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> • as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> • as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> • as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum 	2 Kibyte
number of Multicast stations	16
performance data / S7 communication	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> • maximum 	16
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	32
performance data / PROFINET communication / as PN IO controller	
number of PN IO devices / on PROFINET IO controller / operable / total	32
number of external PN IO lines / with PROFINET / per rack	1
data volume	
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO controller / maximum 	1 Kibyte
<ul style="list-style-type: none"> • as user data for output variables / as PROFINET IO controller / maximum 	1 Kibyte
<ul style="list-style-type: none"> • as user data for input variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
<ul style="list-style-type: none"> • as user data for output variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
<ul style="list-style-type: none"> • as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 	240 byte
<ul style="list-style-type: none"> • as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 	240 byte
performance data / PROFINET communication / as PN IO device	
product function / PROFINET IO device	Yes
data volume	
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO device / maximum 	512 byte
<ul style="list-style-type: none"> • as user data for output variables / as PROFINET IO device / maximum 	512 byte
<ul style="list-style-type: none"> • as user data for input variables / for each sub-module as PROFINET IO device 	240 byte
<ul style="list-style-type: none"> • as user data for output variables / for each sub-module as PROFINET IO device 	240 byte
<ul style="list-style-type: none"> • as user data for the consistency area for each sub-module 	240 byte
number of submodules / per PROFINET IO-Device	32
performance data / telecontrol	
protocol / is supported	

<ul style="list-style-type: none"> • TCP/IP 	Yes
product functions / management, configuration, engineering	
product function / MIB support	Yes
protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • DCP 	Yes
<ul style="list-style-type: none"> • LLDP 	Yes
configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 V5.4 SP2 or higher / STEP 7 Professional V11 (TIA Portal) or higher
identification & maintenance function	
<ul style="list-style-type: none"> • I&M0 - device-specific information 	Yes
<ul style="list-style-type: none"> • I&M1 – higher level designation/location designation 	Yes
product functions / diagnostics	
product function / web-based diagnostics	Yes
product functions / switch	
product feature / switch	Yes
product function	
<ul style="list-style-type: none"> • switch-managed 	No
<ul style="list-style-type: none"> • with IRT / PROFINET IO switch 	Yes
<ul style="list-style-type: none"> • configuration with STEP 7 	Yes
product functions / redundancy	
product function	
<ul style="list-style-type: none"> • ring redundancy 	Yes
<ul style="list-style-type: none"> • redundancy manager 	No
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product functions / security	
product function	
<ul style="list-style-type: none"> • password protection for Web applications 	No
<ul style="list-style-type: none"> • ACL - IP-based 	Yes
<ul style="list-style-type: none"> • ACL - IP-based for PLC/routing 	No
<ul style="list-style-type: none"> • switch-off of non-required services 	Yes
<ul style="list-style-type: none"> • blocking of communication via physical ports 	Yes
<ul style="list-style-type: none"> • log file for unauthorized access 	No
product functions / time	
product function / SICLOCK support	Yes
product function / pass on time synchronization	Yes
protocol / is supported	
<ul style="list-style-type: none"> • NTP 	Yes
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx-Download-Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and

integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

8/3/2021 