

product type designation

RF360T transponder

SIMATIC RF300 Transponder RF360T EPOXY card, 8 KB FRAM, IP67, -25 to +70 °C, 85x 54x 2.5 mm, Minimum order quantity 10 units.



suitability for operation

RF300

radio frequencies

operating frequency / rated value	13.56 MHz
range / maximum	150 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	RF300-specific
transfer rate / with radio transmission / maximum	106 kbit/s
product feature / multitag-capable	Yes

electrical data

product component / backup battery	No
------------------------------------	----

memory

type of memory	FRAM / EEPROM
storage capacity / of the user memory	8189 byte
type of memory organization	UID (fixed code) 4 bytes, user memory 8189 bytes, OTP memory 20 bytes
number of read cycles / at ambient temperature < 40 °C / maximum	1000000000
number of write cycles / at ambient temperature < 40 °C / maximum	1000000000
data retention time / at ambient temperature < 40 °C / not less than	10 y
property of memory	Block-by-block write protection of the OTP memory

mechanical data

material	Epoxy resin
color	anthracite
mounting distance / relating to metal surfaces / recommended / minimum	20 mm

ambient conditions

ambient temperature	-25 ... +75 °C
<ul style="list-style-type: none"> during read/write access outside the read/write area during storage 	-40 ... +85 °C
protection class IP	IP67
shock resistance	According to DIN EN 60721-3-7 Class 7 M3
shock acceleration	500 m/s ²
vibrational acceleration	200 m/s ²
resistance to mechanical stress	Continuous torsion and bending stress not permissible

design, dimensions and weights

width	55 mm
-------	-------

height	2.5 mm
depth	86 mm
net weight	25 g
fastening method	2 x M3 screws, mounting bag (see accessories)
product features, product functions, product components / general	
product feature	
• silicon-free	Yes
• printable	No
standards, specifications, approvals	
certificate of suitability	
• IECEx	No
MTBF	1200 y
accessories	
accessories	Fixing strap, spacer
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	12/18/2020 