



Figure similar

Digital measuring instrument Transmitter SICAM T, Standard mounting rail device without display, Enclosure 96 mm x 96 mm x 100 mm, IP20, 2 binary outputs, Ethernet interface with Modbus TCP, Ohmic voltage divider, 4 analog outputs, serial interface./comm. proto. RS 485/IEC60870-5-103/Modbus RTU

Measuring functions	
measuring procedure / for voltage measurement	resistive voltage divider
sampling frequency / per sampling cycle	3 200 Hz
number of harmonics	0
product function / phase angle measurement	Yes
product function / active power measurement	Yes
product function / reactive power measurement	Yes
product function / apparent power measurement	Yes
product function / querying of limit violations	Yes
product function / logic function	No
type of measured value detection / min./max. values	No
type of measured value detection / mean values	Yes
accuracy class / of the measuring instrument / for measured variable active power / according to IEC 62053-22	0,2S
accuracy class / of the measuring instrument / for measured variable reactive power	0,5
File formats	
type of data transmission / via CSV	No
Energy Management functions	
product function / active energy measurement	Yes
product function / reactive energy measurement	Yes
product function / apparent energy measurement	Yes
Measuring inputs	
number of inputs / for voltage measurement	4
number of inputs / for current measurement	3
input voltage / between L and L / maximum	690 V
input voltage / between L and N / maximum	400 V
input current / maximum	10 A
Supply voltage	
supply voltage / at AC	110 ... 230 V
supply voltage / at DC	24 ... 250 V
measuring range frequency / at the measurement inputs	45 ... 65 Hz
type of voltage / of the supply voltage	AC/DC
Inputs / Outputs	
number of analog inputs	0
number of digital inputs	0
number of analog outputs	4
number of digital outputs	2
Communication	

protocol / is supported / IEC 61850	No
protocol / is supported / Modbus TCP	Yes
protocol / is supported / Modbus RTU	Yes
protocol / is supported / SNMP	No
protocol / is supported / OPC UA with PubSub	No
protocol / is supported / IEC 60870-5-103	Yes
protocol / is supported / IEC 60870-5-104	No
communication function / Modbus RTU as master	No
number of ports / of the Ethernet interface	1
product function / gateway function for Modbus RTU	No

#### Cybersecurity

type of access control / role-based access control (RBAC)	No
product function / logging via Audit log	No
product function / logging via Security Eventlog	No
service / as web server / HTTPS	Yes
product function / firmware identifier	No

#### Time synchronization

type of time synchronization	NTP
------------------------------	-----

#### Mechanical Design

width	96 mm
height	96 mm
depth	100 mm
weight	500 g
fastening method / standard rail mounting	Yes
fastening method / wall mounting	Yes
fastening method / rack mounting	Yes
type of electrical connection	screw-type terminals
connectable conductor cross-section	0.2 ... 2.5 mm <sup>2</sup>

#### Degree of protection / protection class

protection class IP / on the front	IP20
protection class IP / rear side	IP20

#### Environmental conditions

ambient temperature / during operation	-25 ... +55 °C
ambient temperature / during storage	-25 ... +70 °C

#### Approval certification

certificate of suitability / CE marking	Yes
certificate of suitability / UL approval	Yes

#### Further information

**Siemens has decided to exit the Russian market (see here).**

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information- and Downloadcenter (catalogues, leaflets,...)**

<http://www.siemens.com/energy-automation>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KG9661-1FA30-1AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/7KG9661-1FA30-1AA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7KG9661-1FA30-1AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KG9661-1FA30-1AA0)

**Tender specifications**

<http://www.siemens.com/specifications>

