



Main

Range	ARGUS
Product or component type	Occupancy sensor
Load type	Halogen lamp <= 1000 VA Energy saving lamp <= 80 VA Incandescent lamp <= 2000 W Low voltage halogen lamp with conventional transformer <= 1000 VA Low voltage halogen lamp with electronic transformer <= 1000 VA Fluorescent lamp <= 1000 VA LED lamp <= 200 W 1-10 V ballast <= 100 mA HVAC <= 5 A 30 V DC HVAC <= 5 A 250 V AC cos phi = 1

Complementary

Rated voltage	230 V +/- 10 % AC 50/60 Hz
Detection angle	360°
Presence detection area	PIR: 360°, 8 x 8 m
Device mounting	Flush Surface
Mounting support	Ceiling
Mounting height	2...3 m
Diameter	110 mm
Depth	62 mm

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 flush mounting IP54 surface mounting
Ambient air temperature for operation	0...45 °C indoor -20...45 °C outdoor

Packing Units

Package 1 Weight	436.000 g
Package 1 Height	122.000 mm
Package 1 width	117.000 mm
Package 1 Length	177.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------