



### Main

Range	ARGUS
Product or component type	Occupancy sensor
Load type	Halogen lamp <= 1000 VA Energy saving lamp <= 80 VA Incandescent lamp <= 2000 W Low voltage halogen lamp <= 1000 VA Fluorescent lamp 100 µF <= 900 VA HVAC <= 5 A 30 V DC HVAC <= 10 A 250 V AC cos phi = 1

### Complementary

Rated voltage	230 V +/- 10 % AC 50/60 Hz
Detection angle	360°
Presence detection area	PIR: 360°, 8 x 8 m US: 360°, 10 x 16 m
Device mounting	Flush Surface
Mounting support	Ceiling
Mounting height	2...3 m
Diameter	111.5 mm
Depth	72 mm surface mounted 90 mm flush mounting

### Environment

Electrical shock protection class	Class II
IP degree of protection	IP20
Ambient air temperature for operation	0...45 °C
Standards	EN 61000-3-3 EN 60669-1 EN 60669-2-1 EN 61000-3-2 EN 55014 EN 55022

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

**Packing Units**

---

Package 1 Weight	272.000 g
Package 1 Height	128.000 mm
Package 1 width	62.000 mm
Package 1 Length	128.000 mm

---

**Offer Sustainability**

---

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
-------------------	---

---

**Contractual warranty**

---

Warranty	18 months
----------	-----------

---