


NEOZED fuse link 400 V gL/gG, Size D03, 80 A



Model	
Product brand name	SETRON
Product designation	NEOZED fuse link
Product variations	Pack of 10
Design of the fuse link	NEOZED fuse link
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	D03
Operating class of the fuse link	gG
Supply voltage	
• at AC / rated value	400 V
• at DC	250 V
Protection class IP	IP20, with connected conductors
Switching capacity current / acc. to IEC 60947-2 / rated value	50 kA
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	5.4 W
Current / at AC / rated value	80 A

Main circuit	
Operating voltage / rated value	400 V
Operating current / rated value	80 A

Appearance	
Color coding of the fuse link	Blue
Maximum short-circuit current breaking capacity (Icu) / at AC / rated value	50 kA
Mounting position	Any, preferably vertical
Net weight	36 g
Ambient temperature	
• minimum	-5 °C
• maximum	40 °C
Environmental category	Up to 45°C at 95 % rel. humidity

Certificates	
Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F
Waste electronic equipment must not be disposed as unsorted municipal waste, e.g. household waste. For disposing the waste electronic equipment it is necessary to observe the current local national/international regulations.	
	

General Product Approval	Declaration of Conformity	Test Certificates			other
--------------------------	---------------------------	-------------------	--	--	-------



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

[Miscellaneous](#)

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2280>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2280>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2280

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

