

SITOP PSU8200 24 V/10 A  
 SITOP PSU8200 24 V/10 A stabilized power supply input: 120/230 V  
 AC output: 24 V DC/10 A



| Input  |   |
|--|---|
| Input  | 1-phase AC                                  |
| Supply voltage   |   |
| <ul style="list-style-type: none"> <li>• 1 at AC Rated value</li> <li>• 2 at AC Rated value</li> <li>• Note</li> </ul>   | 120 V<br>230 V<br>Automatic range selection |
| Input voltage  |   |
| <ul style="list-style-type: none"> <li>• 1 at AC</li> <li>• 2 at AC</li> </ul>   | 85 ... 132 V<br>170 ... 264 V               |
| Wide-range input   | No  |
| Mains buffering at I <sub>out</sub> rated, min.  | 35 ms; at V <sub>in</sub> = 120/230 V       |
| Rated line frequency 1   | 50 Hz                                       |
| Rated line frequency 2   | 60 Hz                                       |
| Rated line range   | 47 ... 63 Hz                                |
| Input current  |   |
| <ul style="list-style-type: none"> <li>• at rated input voltage 120 V</li> <li>• at rated input voltage 230 V</li> </ul> | 4 A<br>1.9 A                                |
| Switch-on current limiting (+25 °C), max.  | 10 A  |
| I <sup>2</sup> t, max.   | 0.3 A <sup>2</sup> ·s                       |

|   |   |
|---|---|
| Built-in incoming fuse                        | T 6.3 A (not accessible)  |
| Protection in the mains power input (IEC 898) | Recommended miniature circuit breaker at 1-phase operation: from 6 A (10 A) characteristic C (B); required at 2-phase operation: circuit breaker 2-pole connected or circuit breaker 3RV2011-1EA10 (setting 3.8 A) or 3RV2711-1ED10 (UL 489) at 230 V; 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489) at 400/500 V |

## Output

|   |  |
|---|--|
| Output  | Controlled, isolated DC voltage  |
| Rated voltage $V_{out}$ DC  | 24 V   |
| Total tolerance, static $\pm$   | 3 %  |
| Static mains compensation, approx.  | 0.1 %  |
| Static load balancing, approx.  | 0.3 %  |
| Residual ripple peak-peak, max.   | 50 mV  |
| Spikes peak-peak, max. (bandwidth: 20 MHz)  | 200 mV   |
| Adjustment range  | 24 ... 28.8 V  |
| Product function Output voltage adjustable  | Yes  |
| Output voltage setting  | via potentiometer; max. 240 W  |
| Status display  | Green LED for 24 V OK  |
| Signaling   | Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"  |
| On/off behavior   | Overshoot of $V_{out}$ approx. 3 %   |
| Startup delay, max.   | 1 s  |
| Voltage rise, typ.  | 70 ms  |
| Rated current value $I_{out}$ rated   | 10 A   |
| Current range   | 0 ... 10 A   |
| <ul style="list-style-type: none"> <li>Note</li> </ul>  | +60 ... +70 °C: Derating 2%/K; as of $U_a > 24$ V: 4% $[I_a]/V [U_a]$ ; at $U_e < 100$ V/ $< 200$ V: 80% $I_a$ rated |
| Supplied active power typical   | 240 W  |
| Short-term overload current   |  |
| <ul style="list-style-type: none"> <li>at short-circuit during operation typical</li> </ul>       | 30 A   |
| Duration of overloading capability for excess current   |  |
| <ul style="list-style-type: none"> <li>at short-circuit during operation</li> </ul>               | 25 ms  |
| Constant overload current   |  |
| <ul style="list-style-type: none"> <li>on short-circuiting during the start-up typical</li> </ul> | 12 A   |
| Parallel switching for enhanced performance   | Yes; switchable characteristic   |
| Numbers of parallel switchable units for enhanced performance                                     | 2  |

## Efficiency

|   |       |
|---|-------|
| Efficiency at $V_{out}$ rated, $I_{out}$ rated, approx. | 94 %  |
| Power loss at $V_{out}$ rated, $I_{out}$ rated, approx. | 18 W  |
| Power loss [W] during no-load operation maximum         | 1.5 W |

## Closed-loop control

|  |         |
|--|---------|
| Dynamic mains compensation ( $V_{in}$ rated $\pm 15\%$ ), max.                       | 0.1 %   |
| Dynamic load smoothing (I <sub>out</sub> : 50/100/50 %), U <sub>out</sub> $\pm$ typ. | 4 %     |
| Load step setting time 50 to 100%, typ.  | 0.25 ms |
| Load step setting time 100 to 50%, typ.  | 0.5 ms  |
| Dynamic load smoothing (I <sub>out</sub> : 10/90/10 %), U <sub>out</sub> $\pm$ typ.  | 4 %     |
| Load step setting time 10 to 90%, typ.   | 0.25 ms |
| Load step setting time 90 to 10%, typ.   | 0.5 ms  |
| Setting time maximum   | 1 ms    |

### Protection and monitoring

|  |  |
|--|--|
| Output overvoltage protection  | < 33 V   |
| Current limitation, typ.   | 12 A   |
| Property of the output Short-circuit proof   | Yes  |
| Short-circuit protection   | Alternatively, constant current characteristic approx. 12 A or latching shutdown |
| Enduring short circuit current RMS value <ul style="list-style-type: none"> <li>• typical</li> </ul> | 12 A   |
| Overcurrent overload capability in normal operation  | overload capability 150 % I <sub>out</sub> rated up to 5 s/min                   |
| Overload/short-circuit indicator   | LED yellow for "overload", LED red for "latching shutdown"                       |

### Safety

|  |   |
|--|---|
| Primary/secondary isolation  | Yes   |
| Galvanic isolation   | Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178  |
| Protection class   | Class I   |
| Leakage current <ul style="list-style-type: none"> <li>• maximum</li> <li>• typical</li> </ul> | 3.5 mA<br>1 mA  |
| CE mark  | Yes   |
| UL/cUL (CSA) approval  | cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259, cCSAus (CSA C22.2 No. 60950-1, UL 60950-1, UL 1604)                               |
| Explosion protection   | IECEx Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T3 |
| FM approval  | -   |
| CB approval  | Yes   |
| Marine approval  | GL, ABS   |
| Degree of protection (EN 60529)  | IP20  |

### EMC

|                             |                  |
|-----------------------------|------------------|
| Emitted interference        | EN 55022 Class B |
| Supply harmonics limitation | EN 61000-3-2     |
| Noise immunity              | EN 61000-6-2     |

## Operating data

|  |   |
|--|---|
| Ambient temperature  |   |
| <ul style="list-style-type: none"> <li>• during operation</li> <li>— Note</li> <li>• during transport</li> <li>• during storage</li> </ul> | <p>-25 ... +70 °C</p> <p>With natural convection; startup tested starting from -40 °C nominal voltage</p> <p>-40 ... +85 °C</p> <p>-40 ... +85 °C</p> |
| Humidity class according to EN 60721   | Climate class 3K3, no condensation  |

## Mechanics

|  |   |
|--|---|
| Connection technology  | screw-type terminals  |
| Connections  |   |
| <ul style="list-style-type: none"> <li>• Supply input</li> <li>• Output</li> <li>• Auxiliary</li> </ul>    | <p>L, N, PE: 1 screw terminal each for 0.2 ... 2.5 mm<sup>2</sup> single-core/finely stranded</p> <p>+, -: 2 screw terminals each for 0.2 ... 2.5 mm<sup>2</sup></p> <p>13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm<sup>2</sup>;</p> <p>15, 16 (Remote): 1 screw terminal each for 0.14 ... 1.5 mm<sup>2</sup></p> |
| Width of the enclosure   | 55 mm   |
| Height of the enclosure  | 125 mm  |
| Depth of the enclosure   | 125 mm  |
| Required spacing   |   |
| <ul style="list-style-type: none"> <li>• top</li> <li>• bottom</li> <li>• left</li> <li>• right</li> </ul> | <p>50 mm</p> <p>50 mm</p> <p>0 mm</p> <p>0 mm</p>   |
| Weight, approx.  | 1 kg  |
| Product feature of the enclosure housing for side-by-side mounting   | Yes   |
| Installation   | Snaps onto DIN rail EN 60715 35x7.5/15  |
| Electrical accessories   | Buffer module   |
| Mechanical accessories   | Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20   |
| MTBF at 40 °C  | 1 292 102 h   |
| Other information  | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)   |